



# ACETYLENE CYLINDERS

Completely asbestos-free and filled with a high quality glass fiber-reinforced, calcium silicate porous mass.

MODEL	Acetylene Capacity**		Internal Volume	Diameter	Height With Cap	Acetone	Tare Weight (without Cap***)
	ft <sup>3</sup> (m <sup>3</sup> )	lb. (kg)	in <sup>3</sup> (liters)	in. (mm)	in. (mm)	lb. (kg)	lb. (kg)
<b>10 CF (MC)</b>	10 (0.3)	0.7 (0.3)	122 (2.0)	3.8 (96.5)	15.4 (389.9)	1.3 (0.6)	7.7 (3.5)
<b>40 CF (B - Standard)</b>	40 (1.1)	2.7 (1.2)	470 (7.7)	6.0 (152.4)	23.2 (589.2)	5.1 (2.3)	25.2 (11.4)
<b>40 CF (B - Big Flange)*</b>	40 (1.1)	2.7 (1.2)	470 (7.7)	6.0 (152.4)	25.8 (655.3)	5.1 (2.3)	27.9 (12.7)
<b>75 CF</b>	75 (2.1)	5.1 (2.3)	855 (14.0)	7.0 (177.8)	31.3 (795.0)	9.3 (4.2)	43.8 (19.9)
<b>145 CF</b>	145 (4.1)	9.7 (4.4)	1,538 (25.2)	8.0 (203.2)	39.5 (1,003.3)	17.9 (8.1)	72.0 (32.7)
<b>250 CF</b>	250 (7.1)	17.0 (7.7)	2,652 (43.5)	10.0 (254.0)	43.3 (1,099.8)	30.8 (14.0)	117.5 (53.3)
<b>397 CF</b>	397 (11.2)	27.0 (12.2)	4,150 (68.0)	12.3 (312.4)	46.6 (1,183.6)	49.0 (22.2)	170.0 (77.1)
<b>420 CF</b>	420 (11.9)	28.6 (13.0)	4,375 (71.7)	12.3 (312.4)	48.9 (1,242.1)	51.9 (23.5)	177.0 (80.2)
<b>450 CF</b>	450 (12.7)	30.6 (13.9)	4,680 (76.7)	12.3 (312.4)	50.9 (1,292.9)	55.6 (25.2)	185.0 (84.0)

\*All cylinders are DOT-8AL/TC-8WAM – except 40 CF (B - Big Flange) is DOT-8AL only.  
 \*\*At 250 psig and 70°F (17.2 barg and 21°C). \*\*\* Cap weight = add 2 lb. (.9 kg).

**Call us now! (905) 564-8887**

