



Cyl-Tec's Aluminum CO<sub>2</sub> Cylinders — specially designed for the beverage carbonation industry — are light-weight and corrosion-resistant.

## ALUMINUM CO<sub>2</sub> CYLINDERS

Cyl-Tec's Aluminum CO<sub>2</sub> Cylinders have a bare-brushed finish and CGA 320 CO<sub>2</sub> valves as standard. 20 lb. and 50 lb. cylinders include a heavy-duty, reinforced nylon carry handle.

MODEL	Carbon Dioxide (CO <sub>2</sub> )	Service Pressure	Diameter	Height	Weight	Nitrogen (N <sub>2</sub> )	Inlet Thread
	<i>lb. (kg) at 68% fill</i>	<i>psig (bar)</i>	<i>in. (mm)</i>	<i>in. (mm)</i>	<i>lb. (kg)</i>	<i>ft<sup>3</sup> at 70°F (m<sup>3</sup> at 21°C)</i>	
<b>1.5 lb</b>	1.5 (0.68)	1800 (124)	3.2 (82)	11.5 (292)	1.8 (0.83)	4.3 (121.76)	3/4"-16 UNF-2B
<b>2.5 lb</b>	2.5 (1.14)	1800 (124)	4.4 (111)	11.0 (280)	3.7 (1.66)	7.2 (203.88)	3/4"-16 UNF-2B
<b>5 lb</b>	5.0 (2.27)	1800 (124)	5.3 (133)	14.2 (362)	7.5 (3.42)	14.5 (410.59)	1-1/8"-12 UNF-2B
<b>10 lb</b>	10 (4.55)	1800 (124)	6.9 (175)	16.6 (422)	14.1 (6.40)	29.0 (821.19)	1-1/8"-12 UNF-2B
<b>15 lb</b>	15 (6.82)	2215 (153)	7.5 (184)	22.9 (582)	22.3 (10.1)	43.3 (1,226.12)	1-1/8"-12 UNF-2B
<b>20 lb</b>	20 (9.09)	1800 (124)	8.0 (203)	23.3 (592)	24.8 (11.2)	57.6 (1,631.05)	1-1/8"-12 UNF-2B
<b>50 lb</b>	50 (22.7)	1800 (124)	8.6 (218)	46.3 (1,177)	48.8 (22.1)	144.0 (4,077.63)	1-1/8"-12 UNF-2B